



## PERFECT SCORE TECHNOLOGIES

4012 Bronze Way  
Phone (214) 331-0002  
Email: [info@pstmfg.com](mailto:info@pstmfg.com)

Dallas, Texas 75237  
Fax (214) 331-0013  
Web: <http://www.pstmfg.com>

### Hot Melt Clamp

Model: HMC

### Designed for Hot Melt Butyl Sealing of Insulating Glass Units

The PST Hot Melt Clamp Table is engineered to securely hold insulating glass units during hot melt butyl sealing, improving seal quality and operator efficiency. Its heavy-duty pneumatic clamping system firmly secures the glass and spacer while allowing units of virtually unlimited length to be sealed by simply repositioning the glass. Built with rugged steel construction, the table is ideal for high-production insulating glass fabrication.

#### Features & Benefits

- Designed for hot melt butyl sealing of IG units.
- Accommodates **unlimited unit lengths** by allowing lateral repositioning during sealing.
- Seals **single units or stacks up to 4" thick**.
- Heavy-duty all-steel construction for long service life.
- Pneumatic top and bottom clamping system securely holds glass and spacer.
- Foot pedal and hand lever controls provide efficient, hands-free operation.
- Available in **84" x 84"** and **96" x 96"** table sizes.
- Requires only **75 PSI compressed air at 1 CFM**.

| Model     | HOT MELT CLAMP          |                    |
|-----------|-------------------------|--------------------|
|           | Shipping Specifications |                    |
|           | Weight (Lbs.)           | Dimensions (LxWxH) |
| HMC-72X72 | 1050                    | 97 x 88 x 84       |
| HMC-84X84 | 1140                    | 110 x 96 x 84      |
| HMC-96X96 | 1300                    | 124 x 100 x 84     |



#### Technical Highlights

- Available Table Sizes: **72" x 72"**, **84" x 84"** or **96" x 96"**
- Stack Capacity: **Up to 4" thick**
- Air Requirement: **75 PSI @ 1 CFM**
- Pneumatic top and bottom clamping system with neoprene-lined clamp bar

#### Why Choose the PST Hot Melt Clamp Table?

- Produces consistent, high-quality hot melt seals.
- Increases productivity by securely holding the unit during sealant application.
- Handles oversized insulating glass units without length limitations.
- Capable of sealing multiple stacked units to improve production throughput.
- Built for years of dependable operation in demanding IG manufacturing environments.